The Reichert DIGITAL EG-Chek

Why take chances? For precise reading of Ethylene Glycol coolant concentration, hydrometers just don't measure up. The **Reichert Digital EG-Chek** accurately and effectively tests Ethylene Glycol coolant Freeze Point, Boiling Point, and % Concentration. This fast, simple test provides greater peace of mind for your customers while **increasing your service business.**

Our fast, accurate digital tester performs three critical tests on the engine coolant:

Get dependable digital accuracy in a three-in-one tool!



Measures Freeze Point of EG coolant: The Reichert digital EG-Chek's Automatic Temperature Compensation (ATC) provides immediate, accurate, and direct readings at ASTM D3321 standard of +/- 1 degree F and +/- 0.55 degree C. This ensures that the coolant has a low freezing point, so there are no engine block or radiator freeze-ups when the vehicle is not in operation during the cold winter months.

Measures Boiling Point of EG coolant: The engine coolant raises the boiling point of water in a vehicle's cooling system. This guards against boil-overs, engine break-downs, and ensures that the cooling system is operating at peak efficiency (see back).

Measures % Concentration: Measures the exact concentration of the Ethylene Glycol and water mixture to ensure the engine coolant is at the correct chemical specification. Detects for over-concentration or under-concentration of the coolant – either scenario will cause damage to engine components.



www.ReichertAutoTech.com

Analytical Instruments•Automotive&Truck

SPECIFICATIONS:

13940024 (Fahrenheit model) 13940025 (Celsius model)		
Digital Refractometer		
EG Freeze Point, Boiling Point, Percent Concentration		
0 to 95% 0.2%		
(32 to -70 deg F) (1.0 deg F)	(0 to -57 deg C) (0.6 deg C)	
(242 to 356 deg F) (1.0 deg F)	(117 to 180 deg C) (0.6 deg C)	
Distilled Water		
68°F (20°C)		
589nm LED		
54 x 27 x 100 mm / 2.1 x 1.1 x 3.9 inches		
3.5 ounces (100 grams)		
Detachable neck lanyard and rubber side grips for ease of handling		
2 AAA Batteries, included		
10,000 readings, Auto-Off Sleep Mode		
IP65 Dust proof/Water Resistant, CE, RoHS, and WEEE compliant.		
One Year		
Catalog 13941000 (cell phone type availa	ble)	
	13940025 (Celsius mod Digital Refractometer EG Freeze Point, Boilin Percent Concentration 0 to 95% 0.2% (32 to -70 deg F) (1.0 deg F) (242 to 356 deg F) (1.0 deg F) Distilled Water 68°F (20°C) 589nm LED 54 x 27 x 100 mm / 2.1 3.5 ounces (100 grams Detachable neck lanya grips for ease of handl 2 AAA Batteries, includ 10,000 readings, Auto- IP65 Dust proof/Water CE, ROHS, and WEEE co One Year Catalog 13941000	

Reichert DIG	325	
Part# 13940013	Description DEF-Chek® digital model (% Urea)	
Reichert DI	GITAL <i>Multi-Chek</i> °	
Part#	Description	Akiti-Chek
13940014	Multi-Chek [®] digital model (Fahrenheit)	See 2 See 2
13940015	Multi-Chek [®] digital model (Celsius)	Biofest carrie
Reichert DI	2845	
Part#	Description	an and a set of the se

Part#	Description
13940016	Brake-Chek [®] digital model (Fahrenheit)
13940017	Brake-Chek [®] digital model (Celsius)

Reichert DIGITAL Glycerin, EG, PG-Chek

Part#	Description	Ghe
13940022	Glycerin-Chek digital model (Fahrenh	eit) 🔣
13940023	Glycerin-Chek digital model (Celsius)	N. THEY MANY
13940024	EG-Chek digital model (Fahrenheit)	CIT
13940025	EG-Chek digital model (Celsius)	-56F
13940026	PG-Chek digital model (Fahrenheit)	Ga Ca Ca
13940027	PG-Chek digital model (Celsius)	Aufert anna

The Reichert DIGITAL EG-Chek

The basics of proper coolant control

In an internal combustion engine, a lot of heat is generated and some of it is absorbed into the engine. The engine runs best when the engine coolant is 200 degrees Fahrenheit or 93 degrees Celsius. At this temperature:

- The combustion chamber is hot enough to completely vaporize the fuel which provides better combustion and reduced emissions
- The oil used to lubricate the engine has a lower viscosity so the engine parts move more freely and the engine wastes less power moving its components
- Metal parts wear less

For the engine coolant to effectively do its job, it must have the correct concentration of the Ethylene Glycol and water. The concentration changes both the Freeze Point and the Boiling Point of the coolant.

The Reichert digital EG-Chek – the fast, accurate, state-of-the-art choice over ineffective hydrometers and test strips.

Just how inaccurate are hydrometers?

 According to ASTM method D1124, the BEST accuracy that is achievable with a laboratory certified hydrometer in a controlled environment is +/- 8 degrees F. But, the field hydrometers commonly sold and used in the automotive service industry are not laboratory certified and have been found to be *inaccurate by as much as +/- 23 degrees F*.

Just how accurate is the Reichert digital EG-Chek?

• The Reichert EG-Chek meets ASTM D3321 standard for measuring engine coolant freeze point using a refractometer. The ASTM standard specifies a required accuracy of +/- 1 degree F and +/- 0.55 degree C. Need we say more?

The Reichert digital EG-Chek, the clear solution!

• The Reichert EG-Chek is extremely economical to operate, providing 10,000+ measurements on two AAA batteries.



MERCOFRAMES OPTICAL CORP

5555 Nw 74 Ave. Miami. Fl. 33166 www.mercoframes.net ale@mercoframes.net

